

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/pera

DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY AFFAIRS (PERA)

BOARD AND CODE ADMINISTRATION DIVISION

# **NOTICE OF ACCEPTANCE (NOA)**

Eurotech Industries, Inc. 4201 NE 12<sup>th</sup> Terrace Ft. Lauderdale, FL 33334

#### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

### **DESCRIPTION:** Outswing Aluminum Casement Window – L.M.I.

APPROVAL DOCUMENT: Drawing No. W03-80, titled "Aluminum Casement Window (L.M.I.)", sheets 1 through 5 of 5, dated 09/05/03, with revision D dated 10/19/11, prepared by Al-Farooq Corporation, signed and sealed by Javad Ahmad, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

### MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA revises NOA # 08-1112.08 and consists of this page 1 and evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Manuel Perez, P.E.

MIAMI-DADE COUNTY
APPROVED

14/10/12

NOA No. 12-0207.03 Expiration Date: February 05, 2014 Approval Date: April 19, 2012 Page 1

### Eurotech Industries, Inc.

### NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

### A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- 2. Drawing No. W03-80, titled "Aluminum Casement Window (L.M.I.)", sheets 1 through 5 of 5, dated 09/05/03, with revision D dated 10/19/11, prepared by Al-Farooq Corporation, signed and sealed by Javad Ahmad, P.E.

#### B. TESTS

- 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94
  - 4) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of aluminum casement

windows mulled side-by-side, prepared by Hurricane Engineering & Testing Inc., Test Report No. **HETI-03-1315**, dated 05/12/03, signed and sealed by Rafael E. Droz-Seda, P.E.

## (Submitted under previous NOA # 06-1019.03)

- 2. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
  - 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of aluminum casement windows mulled side-by-side, prepared by Hurricane Engineering & Testing Inc., Test Report No. **HETI-03-1829**, dated 05/12/03, signed and sealed by Rafael E. Droz-Seda, P.E.

# (Submitted under previous NOA # 06-1019.03)

- 3. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94
  - 4) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of a single aluminum casement window, prepared by Hurricane Engineering & Testing Inc., Test Report No. **HETI-03-1317**, dated 05/14/03, signed and sealed by Rafael E. Droz-Seda, P.E (Submitted under previous NOA # 06-1019.03)
- 4. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
  - 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of single aluminum casement windows, prepared by Hurricane Engineering & Testing Inc., Test Report No. **HETI-03-1822**, dated 01/23/04, signed and sealed by Rafael E. Droz-Seda, P.E. (Submitted under previous NOA # 06-1019.03)

Manuel Jeff Manuel Perez, H.E. Product Control Examiner NOA No. 12-0207.03

Expiration Date: February 05, 2014

Approval Date: April 19, 2012

# Eurotech Industries, Inc.

## NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

#### C. CALCULATIONS

- 1. Anchor verification calculations and structural analysis, complying with FBC-2004 and 2007 dated 10/07/08, updated to the FBC-2010, prepared by Al-Farooq Corporation, dated 10/18/11, signed and sealed by Javad Ahmad, P.E. (Submitted under previous NOA#08-1112.08)
- 2. Glazing complies with ASTM E1300-04

#### D. QUALITY ASSURANCE

1. Miami-Dade Department of Permitting, Environment, and Regulatory Affairs (PERA).

#### E. MATERIAL CERTIFICATIONS

- 1. Notice of Acceptance No. 11–0624.02 issued to E.I. DuPont DeNemours & Co., Inc. for their "DuPont SentryGlas® Interlayer" dated 08/25/11, expiring on 01/14/17.
- 2. Notice of Acceptance No. 11-0325.05 issued to Solutia, Inc. for their "Saflex and Vanceva clear and color interlayers" dated 05/05/11, expiring on 05/21/16.

### F. STATEMENTS


1. Statement letter of conformance, complying with FBC-2010, and of no financial interest, dated October 18, 2011, signed and sealed by Javad Ahmad, P.E.

### G. OTHER

1. Notice of Acceptance No. **08-1112.08**, issued to Eurotech Industries, Inc. for their Outswing Aluminum Casement Window – L.M.I., approved on 03/11/09 and expiring on 02/05/14.

Manuel Perez, R.E.
Product Control Examiner
NOA No. 12-0207.03

Expiration Date: February 05, 2014 Approval Date: April 19, 2012




# ALUMINUM CASEMENT WINDOW (IMPACT)

DESIGN LOAD RATING FOR THESE WINDOWS TO BE AS PER CHARTS SHOWN ON SHEET 2.

APPROVAL APPLIES TO SINGLE VENT WINDOWS OR DUAL VENT WINDOWS USING INTEGRAL IMPOST.

ALSO SIDE BY SIDE COMBINATIONS OF CASEMENT/CASEMENT OF TWO OR MORE WINDOWS USING APPROVED MULLIONS.



THIS PRODUCT HAS BEEN DESIGNED AND TESTED TO COMPLY WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE 2010 EDITION INCLUDING HIGH VELOCITY HURRICANE ZONE (HVHZ).

WOOD BUCKS BY OTHERS, MUST BE ANCHORED PROPERLY TO TRANSFER LOADS TO THE STRUCTURE.


ANCHORS SHALL BE AS LISTED, SPACED AS SHOWN ON DETAILS, ANCHORS EMBEDMENT TO BASE MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO.

ANCHORING OR LOADING CONDITIONS NOT SHOWN IN THESE DETAILS ARE NOT PART OF THIS APPROVAL.

A LOAD DURATION INCREASE IS USED IN DESIGN OF ANCHORS INTO WOOD ONLY.

MATERIALS INCLUDING BUT NOT LIMITED TO STEEL/METAL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF 2010 FLORIDA BLDG. CODE SECTION 2003.8.4.

WINDOWS GLAZED WITH LAMINATED GLASS RATED FOR LARGE MISSILE IMPACT AND DO NOT REQUIRE SHUTTERS.



PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No 12-0207.03
Expiration Date FEB. 5,7014

Expiration Date FEB.5.2014

Sy Mauric Start

Miami Dade Product Control

dote: 09–05–03

| cole: 1/2"=1'-0" | Cole of the cole: 09 | C

drawing no.

sheet 1 of 5

DESIGN LOAD CAPACITY - PSF FOR ( X ) SIZES										
		GLASS TYPE 'A'				GLASS TYPE 'B'				
WINDOW DIMS.		JAMB ANCHORS AT 16" O.C.		JAMB ANCHORS AT 8" O.C.		JAMB ANCHORS AT 16" O.C.		JAMB ANCHORS AT 8" O.C.		
WIDTH	HEIGHT	EXT.(+)	1NT.(-)	EXT.(+)	1NT.(-)	EXT.(+)	1NT.(-)	EXT.(+)	1NT.(-)	
19-1/8"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
26-1/2"	26"	75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
37"		75.0	75.0	75.0	75.0	75.0	85.3	75.0	90.0	
19-1/8"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
26-1/2"	38-3/8"	75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
37"		75.0	75.0	75.0	75.0	75.0	77.1	75.0	90.0	
19-1/8"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
26-1/2"	50~5/8"	75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
37"		73.0	73.0	75.0	75.0	73.0	73.0	75.0	90.0	
19-1/8"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
26-1/2"	63"	75.0	75.0	75.0	75.0	75.0	81.9	75.0	90.0	
37"		58.7	58.7	75.0	75.0	58.7	58.7	75.0	90.0	
19-1/8"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
26-1/2"	74"	75.0	75.0	75.0	75.0	75.0	83.7	75.0	90.0	
37"		-	-	-	-	60.0	60.0	75.0	90.0	
18"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
24"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
30"	24"	75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
36"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
18"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
24"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
30"	36"	75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
36"		75.0	75.0	75.0	75.0	75.0	84.4	75.0	90.0	
18"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
24"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
30"	48"	75.0	75.0	75.0	75.0	75.0	76.0	75.0	90.0	
36"		63.3	63.3	75.0	75.0	63.3	63.3	75.0	90.0	
18"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
24"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
30"	60"	75.0	75.0	75.0	75.0	75.0	76.0	75.0	90.0	
36"		63.3	63.3	75.0	75.0	63.3	63.3	75.0	90.0	
18"		75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
24"	72"	75.0	75.0	75.0	75.0	75.0	90.0	75.0	90.0	
30"	'*	75.0	75.0	75.0	75.0	75.0	76.0	75.0	90.0	
36"		-	_	-		63.3	63.3	75.0	90.0	

90.0	-3/16" HEAT STREN'D GLASS	←3/16" HEAT STREN'D GLASS					
90.0	.090" INTERLAYER	.100" INTERLAYER					
	SAFLEX/KEEPSAFE BY 'SOLUT						
	3/16" HEAT STREN'D GI	ASS \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \					
전 표   구	SILICONE  GE SCS 2800	SILICONE GE SCS 2800					
3/4" MIN. TY GLASS BITE	6	GLASS BITE  GLASS BITE					
3/4 G		4, 6					
EXTERIOR		ST CALLEGE WINDS AND					
Ä	GLASS TYPE 'A'	ä GLASS TYPE 'B'					
GLAZING OPTIONS							

		GLASS TYPE 'A' & 'B'					
		JAMB ANCHORS AT 16" O.C.					
WINDO	y dims.		AT EACH IMPOST	3 ANCHORS AT EACH SIDE OF IMPOST			
WIDTH	HEIGHT	EXT.(+)	1NT.(-)	EXT.(+)	1NT.(-)		
26-1/2"		75.0	75.0	75.0	75.0		
37"	26"	75.0	75.0	75.0	75.0		
53-1/8"	20	75.0	75.0	75.0	75.0		
74"		75.0	75.0	75.0	75.0		
26-1/2"		75.0	75.0	75.0	75.0		
37"	797/9"	75.0	75.0	75.0	75.0		
53-1/8"	30-3/6	75.0	75.0	75.0	75.0		
74"		75.0	75.0	75.0	75.0		
26-1/2"		75.0	75.0	75.0	75.0		
37"	505 /8"	75.0	75.0	75.0	75.0		
53-1/8"	63"	75.0	75.0	75.0	75.0		
74"		65.7	65.7	75.0	75.0		
26-1/2"	63"	75.0	75.0	75.0	75.0		
37"		75.0	75.0	75.0	75.0		
53-1/8"		73.6	73.6	75.0	75.0		
74"		52.8	52.8	61.0	61.0		
24"		75.0	75.0	75.0	75.0		
36"	26" 38-3/8" 50-5/8"	75.0	75.0	75.0	75.0		
48"		75.0	75.0	75.0	75.0		
60"		75.0	75.0	75.0	75.0		
72"		75.0	75.0	75.0	75.0		
24"		75.0	75.0	75.0	75.0		
36"		75.0	75.0	75.0	75.0		
48"	36"	75.0	75.0	75.0	75.0		
60"		75.0	75.0	75.0	75.0		
72"		75.0	75.0	75.0	75.0		
24"		75.0	75.0	75.0	75.0		
36"		75.0	75.0	75.0	75.0		
48"	48"	75.0	75.0	75.0	75.0		
60"		75.0	75.0	75.0	75.0		
72"		71.3	71.3	75.0	75.0		
24"		75.0	75.0	75.0	75.0		
36"		75.0	75.0	75.0	75.0		
48"	60"	75.0	75.0	75.0	75.0		
60"		68.4	68.4	75.0	75.0		
72"		57.0	57.0	72.6	72.6		

DESIGN LOAD CAPACITY - PSF FOR ( XX ) SIZES

Engr: JAVAD AHMAD | CIVIL | FLA. PE # 70592 C.A.N. 3538

NOV 2 1 2011

ERODUCT REVISED
as complying with the Florida
Building Code
Acceptance No 12-0207.03
Expiration Date FEB. 5, 2014
By Mami Dade Product Control

1		1					ı	
	revisions:	date	01-10.04	90'60'90	10.06.08	10.19.11		
	(ē)	9	٧	В	O	٥		
1	$\subseteq$	7		57		77	-	
3 14	date: 09-05-03		scole: 1/2" = 1"		dr. by: HAMID			
	drawing no							
			0.		-8	30		

| scole: 1/2" = 1" | dr. by: HAMID | chk. by: W03-80

sheet 2 of 5


drawing no.

AL-FAROOQ CORPORATION
ENGINEERS & PRODUCT DEVELOPMENT
1235 S.W. 87 AVE
MIAMI, FLORIDA 33.174
TEL (305) 264-8100 FAX. (305) 262-6978

ALUMINUM CASEMENT WINDOW (L.M.I.)

EUROTECH INDUSTRIES INC.
4201 N.E. 12TH TERRACE
FT. LAUDERDALE, FL. 33334
TEL. (954) 630-9967 FAX. (954) 630-0217

NOTE: GLASS CAPACITIES ON THIS SHEET ARE BASED ON ASTM E1300-04 (3 SEC. GUSTS) AND FLORIDA BUILDING COMMISSION DECLARATORY STATEMENT DCA05-DEC-219



er<sub>C</sub>

(, (305) 262-6978

FAROOQ CORPORATION
EERS & PRODUCT DEVELOPMENT
S.W. 87 AVE
FLORIDA 33174

ENGINEERS & F 1235 S.W. 87 A MIAMI, FLORID.

EUROTECH INDUSTRIES INC. 4201 N.E. 12TH TERRACE FT. LAUDERDALE, FL. 33334 TEL. (954) 630–9967 FAX. (954) 630–

by description

No CHANGE THIS SHEET

UPDATED FOR 2004 FBC

4201

HT. I

drawing no.

sheet 3 of 5

